

# ADCAP VACUUM TECHNOLOGY

## Power Feedthrough

### 5-15KV Rating Power Feedthrough

- Voltage rating 5-15KV
- Threaded End conductor Rod
- Constructed Materials are UHV compatible
- Beakable= $\geq 450^{\circ}\text{C}$  (Operatable@ $350^{\circ}\text{C}$ ) (注)
- Leak rate= $\geq 2 \times 10\text{E-}8$  (Pa)

#### Rod Conductor 6mm (M6 Threaded both Vacuum and Air side)



サイズ				規格／型式
Flange	導体材質	VOLTS	AMPS	
CF70	Stainless	5KV	25	EFR5-C35-1S
CF70	Nickel	5KV	70	EFR5-C35-1N
CF70	OFHC Copper	5KV	150	EFR5-C35-1C
CF70	Stainless	10KV	25	EFR10-C35-1S
CF70	Nickel	10KV	70	EFR10-C35-1N
CF70	OFHC Copper	10KV	150	EFR10-C35-1C
CF70	Stainless	15KV	25	EFR15-C35-1S
CF70	Nickel	15KV	70	EFR15-C35-1N
CF70	OFHC Copper	15KV	150	EFR15-C35-1C



サイズ				規格／型式
Flange	導体材質	VOLTS	AMPS	
CF70	Stainless	5KV	25	EFR5-C35-2S
CF70	Nickel	5KV	70	EFR5-C35-2N
CF70	OFHC Copper	5KV	150	EFR5-C35-2C
CF70	Stainless	10KV	25	EFR10-C35-2S
CF70	Nickel	10KV	70	EFR10-C35-2N
CF70	OFHC Copper	10KV	150	EFR10-C35-2C
CF70	Stainless	15KV	25	EFR15-C35-2S
CF70	Nickel	15KV	70	EFR15-C35-2N
CF70	OFHC Copper	15KV	150	EFR15-C35-2C



■各種の高真空導入端子の製作に対応を致します。詳細を明記の上、弊社までお知らせください。